



**PT60
Narvalo**
Windows mobile
computer

FEATURES

Windows CE Operating System.

Built to work with Windows CE, the PT60 Narvalo can support your technology environment perfectly.

Uninterrupted Productivity.

Equipped with a 3,800 mAh battery, the PT60 Narvalo lasts an average of 10 hours. For scan intensive workdays, a cradle with spare battery charging slot can be used to ensure a full charge is always on hand.

Stay Connected.

The PT60 Narvalo is equipped with WiFi (802.11b/g/n, 2.4 Ghz) that supports up to 54Mbps. Additionally, it is possible to communicate with other devices through Bluetooth.

Less Weight, more Comfort.

At only 303g (including battery), this mobile computer brings all day comfort to your operations. Its physical keyboard combined with a crystal clear 3.7 inch touch screen allows workers to navigate the device with ease.

Effortless out of the Box Experience.

Take the PT60 Narvalo out of the box and get started right away. The device comes ready to use and configuration is quick and simple, minimizing the time needed to set up the devices.



Charging cradle.

Application Scenarios

Transport and Logistics (Warehouse, Backoffice) • Retail (Warehouse, Backoffice, Store) • Manufacturing (Operational Data Collection) • Healthcare (Patient Care, Laboratory and pharmacy).

PT60 Narvalo

Windows mobile computer

newland-id.com

| | | | | |
|-------------------------|-----------------------|--|---|--|
| Performance | Processor | | Marvell XScale PXA310, 806MHz CPU | |
| | Operating System | | Microsoft Windows CE.NET 6.0 | |
| | Memory | 256MB RAM | | |
| | | 128MB ROM | | |
| | | | 4GB flash memory for user storage | |
| Interface | | Micro USB 2.0, Battery charging over USB supported | | |
| Physical | Dimensions | | 166(L) ×73(W) ×26(H) mm | |
| | Weight | | 303g (including battery) | |
| | Display | | 3.7" WVGA with backlight TFT touch screen | |
| | Keypad | | 33 keys (side keys included) with backlight | |
| | Notification | | Vibrator, speaker and multi-color LEDs | |
| | Battery | Main | 3.7V, 3800mAh rechargeable Li-Polymer battery | |
| | | Backup | 3.7V, 150mAh rechargeable Li-Polymer battery (supports 50-hour data backup) | |
| | Expected Battery Life | | 10 hours (1 scan per second) | |
| | Expansion | | MicroSD card slot (max. 32GB) | |
| | AC Adapter | | Output: DC5V, 1.5A Input: AC100~240V, 50~60Hz | |
| Environmental | Operating Temperature | | -10°C to 50°C (-14°F to 122°F) | |
| | Storage Temperature | | -20°C to 60°C (-4°F to 140°F) | |
| | Humidity | | 5% to 95% (non-condensing) | |
| | Static Discharge | | ±15 kV (Air discharge), ±8 kV (Direct discharge) | |
| | Drop | | 1.2m | |
| | Sealing | | IP54 | |
| Barcode Scanning | 1D Barcode | Laser (≥4mil) CCD (≥4mil) | Code 128, EAN-13, EAN-8, Code 39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5, ISBN/ISSN, Code 93, etc. | |
| | 2D Barcode | CMOS(≥5mil) | All major 1D symbologies, PDF417, QR Code, Data Matrix, Maxicode, Aztec, etc. | |
| Wireless | WLAN RADIO | | IEEE 802.11 b/g/n, security supports EAP, WEP, WPA, WPA2 | |
| | WPAN RADIO | | Bluetooth Class II V2.0 | |
| Certifications | | FCC Part15 Class B, CE EMC Class B, CCC | | |
| Accessories | | Cradle, battery, AC adapter, USB cable, stylus | | |

*Specifications are subject to change without notice.

Newland EMEA HQ
+31 (0) 345 87 00 33
info@newland-id.com
newland-id.com

D-A-C-H
+49 (0) 6182 82916-16
info@newland-id.de

United Kingdom
+44 (0) 1442 212020
sales@newland-id.co.uk

France
+39 (0) 345 8804096
france@newland-id.com

Russia
+31 (0) 345 87 00 33
russia@newland-id.com

Benelux
+31 (0) 345 87 00 33
benelux@newland-id.com

Turkey
+90 (0) 544 538 40 49
turkey@newland-id.com

Ibérica
+34 (0) 93 303 74 66
info@newland-id.es

Middle East
+39 (0) 345 8804096
middleeast@newland-id.com

Italy
+39 (0) 342 0562227
italy@newland-id.com

South Africa
Gauteng: +27 (0) 11 553 8010
Cape Town: +27 (0) 21 9140819
info@newland-id.co.za

Nordic & Baltic
+46 (0) 70 88 47 767
nordic@newland-id.com
info@newland-id.com

Iran
+90 (0) 544 538 40 49
iran@newland-id.com