



**FR4060**  
**Akame**  
fixed mount  
barcode scanner

## FEATURES

### Quick to switch mode.

The Scan Mode Switch at the top of the scanner allows users to swiftly toggle between the Regular and Screen modes.

### Superior motion tolerance.

Exceptional motion tolerance (2.5m/s) and large FOV (46°) enhance user experience.

### IP50 rated sealing.

An IP50-rated seal renders the scanner impervious to dust, water and other contaminant.

### Superb reading performance.

Armed with Newland's fifth-generation of UIMG technology, the FR4060 is capable of reading 1D as well as high-volume 2D barcodes on the screen covered with protective film.

### 1.2m drop resistance.

The scanner withstands multiple 1.2m drops to concrete (six sides, one drop per side).

### IR trigger.

The IR sensor in the scanner enables speedy capture of barcodes presented to it, markedly increasing throughput and productivity.

## Application Scenarios

POS • customer service desk • ticket validators • O2O.

# FR4060 Akame

## fixed mount barcode scanner

newland-id.com

<b>Performance</b>	Image Sensor		CMOS	
	Pixels		752*480 CMOS	
	Symbologies	2D	PDF417, QR Code, Data Matrix, Chinese Sensible Code, etc.	
		1D	EAN-13, EAN-8, UPC-A, UPC-E, ISSN, ISBN, Codabar, Code 128, Code 93, ITF-6, ITF-14, Interleaved 2 of 5, Industrial 2 of 5, Standard 2 of 5, Matrix 2 of 5, GS1 Databar, Code 39, Code 11, MSI-Plessey, Plessey, etc.	
	Resolution		≥5mil	
	Motion Tolerance		2.5m/s	
	Scan Angle	Pitch	±60°@ 0°Roll and 0° Skew	
		Roll	±360°@ 0°Pitch and 0° Skew	
		Skew	±55°@ 0°Roll and 0° Pitch	
	Symbol Contrast		≥25%	
	Interface		RS-232, USB	
	<b>Physical</b>	Dimensions (L×W×H)		83×81×148mm
		Weight		292g
Notification		Beep, LED indicator		
Current		Operating	150mA	
		Standby	120mA	
<b>Environmental</b>	Operating Temperature		-20°C~50°C	
	Storage Temperature		-40°C~70°C	
	Humidity		5%~95% (non-condensing)	
	ESD		±14 kV (air discharge), ±8 kV (direct discharge)	
	Drop		1.2m drops to concrete (for six sides, one drop per side)	
	Sealing		IP50	
<b>Certifications</b>	FCC Part15 Class B , CE EMC Class B			
<b>Accessories</b>	Cable	USB	Used to connect the FR40 to a host device.	
		RS-232	Equipped with a power connector; used to connect the FR40 to a host device.	
	Power Adaptor	Used to provide power for the FR40. Output: DC5V, 1.5A; Input: AC100~240V, 50~60Hz		

\*Specifications are subject to change without notice.\*

Version: V1.0

### Newland EMEA HQ

+31 (0) 345 87 00 33  
info@newland-id.com  
newland-id.com

### D-A-C-H

+49 (0) 6182 82916-16  
info@newland-id.de

### United Kingdom

+44 (0) 7771 631387  
info@newland-id.co.uk

### France

+39 (0) 345 8804096  
france@newland-id.com

### Russia

+31 (0) 345 87 00 33  
russia@newland-id.com

### Benelux

+31 (0) 345 87 00 33  
benelux@newland-id.com

### Turkey

+90 (0) 544 538 40 49  
turkey@newland-id.com

### Ibérica

+34 (0) 93 303 74 66  
info@newland-id.es

### Middle East

+39 (0) 345 8804096  
middleeast@newland-id.com

### Italy

+39 (0) 342 0562227  
italy@newland-id.com

### South Africa

Gauteng: +27 (0) 11 553 8010  
Cape Town: +27 (0) 21 9140819  
info@newland-id.co.za

### Nordic & Baltic

+46 (0) 70 88 47 767  
nordic@newland-id.com

### Iran

+90 (0) 544 538 40 49  
iran@newland-id.com