



FEATURES

Scan virtually any barcode.

Streamline and optimize your production line with the HR42-SR Halibut. Using advanced technology, the device enhances the scanning of virtually every 1D and 2D barcode printed on paper, plastic and metal, as well as a range of direct part marks (DPMs).

Unrivalled performance.

With its megapixel camera, the HR42-SR Halibut raises the bar for handheld scanners. It is able to read small, dense barcodes and damaged barcodes faster and more accurately, ensuring maximum productivity no matter what.

User-friendly aiming technology.

Designed with the end user in mind, the HR42-SR has a crisp and accurate laser aimer for point-and-shoot scanning.

Rock-solid architecture.

Your employees can confidently use the HR42-SR Halibut all day everyday due to its drop resistant housing (1.8m). Designed for light industrial environments, the HR42-SR Halibut just works, even if they bump or drop it.

Available with autosense stand as an accessory or as a SET.



HR42-SR with autosense stand.

Application Scenarios

Light-industrial applications • including electronic assembly • production line • healthcare • postal and financial.

HR42-SR Halibut handheld barcode scanner

newland-id.com

| | | | | |
|-----------------------------------|------------------------------------|--|---|--|
| Performance | Image Sensor | 1280×960 CMOS | | |
| | Illumination | White LED | | |
| | Aiming | 650nm laser diode | | |
| | Symbologies | 2D | PDF417, QR Code, Data Matrix, Aztec, Maxicode, etc. | |
| | | Postal | USPS Postnet, Royal Mail, KIX Post, Australian Postal, etc. | |
| | | 1D | EAN-13, EAN-8, UPC-A, UPC-E, ISSN, ISBN, Codabar, Code 128, Code93, ITF-6, ITF-14, Interleaved 2 of 5, Industrial 2 of 5, Standard 2 of 5, Matrix 2 of 5, GS1 Databar, Code 39, Code 11, MSI-Plessey, Plessey, etc. | |
| | Resolution* | ≥3mil | | |
| | Typical Depth of Field* | EAN-13 | 40mm-410mm | |
| | | Code 39 | 110mm-250mm | |
| | | PDF417 | 115mm-190mm | |
| | | Data Matrix | 100mm-250mm | |
| | | QR Code | 70mm-280mm | |
| | Motion Tolerance* | 2m/s | | |
| | Scan Angle** | Pitch: ±50°, Roll: 360°, Skew: ±50° | | |
| | Field of View | Horizontal 40.5°, Vertical 30.4° | | |
| Symbol Contrast* | ≥25% | | | |
| Mechanical/ Electrical | Interfaces | RS-232, USB, PS/2 | | |
| | Dimensions | 74.0(W)×115.0(D)×161.0(H)mm | | |
| | Weight | 173g | | |
| | Notification | Beep, LED indicator, vibration | | |
| | Rated Power Consumption | 1251mW (typical) | | |
| | Operating Voltage | 5VDC±5% | | |
| | Current@5VDC | Operating | 266mA (typical), 344mA (max.) | |
| | | Standby | 109mA | |
| Environmental | Operating Temperature | -20°C to 50°C (-4°F to 122°F) | | |
| | Storage Temperature | -40°C to 70°C (-40°F to 158°F) | | |
| | Humidity | 5%~95% (non-condensing) | | |
| | ESD | ±8 KV (contact discharge); ±16 KV (air discharge) | | |
| | Drop | 1.8m | | |
| | Sealing | IP42 | | |
| Certifications | FCC Part15 Class B, CE EMC Class B | | | |
| Accessories | Cable | USB | Used to connect the HR42 to a host device. | |
| | | RS-232 | Used to connect the HR42 to a host device. | |
| | Power Adapter | DC5V power adapter to power the HR42 with RS-232 cable. Output: DC5V, 1.5A Input: AC100-240V, 50-60Hz | | |

*Test conditions: T=23°C; Illumination=300lux using incandescent lamp; sample barcodes made by Newland.

Version: V1.0

**Test conditions: Scan Distance= (min. DOF + max. DOF)/2; T=23°C; Illumination=300lux using incandescent lamp; 2D: QR Code; 10 Bytes; Resolution=15mil; PCS=0.8.

Specifications are subject to change without notice.

Newland EMEA HQ
+31 (0) 345 87 00 33
info@newland-id.com
newland-id.com

D-A-C-H
+49 (0) 6182 82916-16
info@newland-id.de

United Kingdom
+44 (0) 1442 212020
sales@newland-id.co.uk

France
+39 (0) 345 8804096
france@newland-id.com

Russia
+31 (0) 345 87 00 33
russia@newland-id.com

Benelux
+31 (0) 345 87 00 33
benelux@newland-id.com

Turkey
+90 (0) 544 538 40 49
turkey@newland-id.com

Ibérica
+34 (0) 93 303 74 66
info@newland-id.es

Middle East
+39 (0) 345 8804096
middleeast@newland-id.com

Italy
+39 (0) 342 0562227
italy@newland-id.com

South Africa
Gauteng: +27 (0) 11 553 8010
Cape Town: +27 (0) 21 9140819
info@newland-id.co.za

Nordic & Baltic
+46 (0) 70 88 47 767
nordic@newland-id.com

Iran
+90 (0) 544 538 40 49
iran@newland-id.com