

Firefly Series

P080UG

P080UP



8" Rimless POS LCD Monitor



Features

1. Rimless front bezel design, spill & dust proof, meets IP54 requirement
2. Integrated protection glass (Model : P080UG) or P Cap Flat Touch (P080UP)
3. Small footprint
4. VESA 75 x 75 mm wall mounting standard
5. Sleek surface throughout monitor's appearance
6. Flexible height adjustment without tool
7. Smart cable management
8. Viewing angle adjustment up to 120° (L/R) / 30° (upward)
9. Low power consumption only 2.5W with LED backlight

Specification

Model	P080UG / P080UP	
Cabinet Color	Black or White	
Cover Lens	P080UG	Mitsubishi PMMA Hardness > 2H (JIS D0202), T > 93%
	P080UP	P Cap Flat Touch
Display Type	8" diagonal TFT active matrix with LED backlight	
Recommended Resolution	800 x 600	
Brightness	250 cd/m ² (typ.)	
Contrast Ratio	500:1 (typ.)	
Viewing Angle	125° (H) / 140° (V)	
I/O Connectivity	USB-B	
Backlight MTBF	20,000 hrs	

* Specification is subject to be changed without prior notice.



Application

Supermarket
Chain stores
Hospitality
Factory automation



Dimension (unit: mm)

