

MONITOR TÁCTIL RESISTIVO 19” T9AV2



Specification

Panel size	19 inch TFT- LCD Touch Screen Monitor
Display ratio	4:3
Standard Resolution	1280*1024
Number of Colors	16.7M
Brightness	250cd/ m ²
Response time	2ms
View angle	Horizontal: 80° Vertical: 70°
Contraseratio	1000:1
Interface	VGA for video signal USB for touch
Frequency	30~80KHz/60~75Hz
Power supply	External Power Supply:100 to 240V (DC 12V)
Operation Environment	Workable Temperature:- 10 to 60°C Storage temperature :- 20 to 70°C Operate relative humidity :20%to 80%storage relative humidity :10%to 90%
Touch mode	5 wire resistive touch
Optional	(4 wire resistive touch ,SAW,Infrared touch,etc optional)
Duration	50000hours
touch validity	>1,000,000
Mount (optional)	1) Mounting Holes: VESA 75mm&100mm 2) provide stable metal base to support the monitor
OSD control	AUTO,+,POWER,- ,MENU brightness,contrast ratio ,auto adjustment ,phase position,clock ,Languages,function,Instal,reset
Touchinterface	USB
Touch response time	2ms
Warranty	3 years
Supporting OS.	Windows,Linux ,Mac.