



Highlights & Data Sheet



HIGHLIGHTS

- Monochrome 4,5" (11,4 cm) TFT with optional backlight.
- Extremely robust hardened sensor surface made of special glass (8H) with ER-technology.
- Flat, light and cost-efficient build for stationary and mobile usage.
- Unique RSA-signature creation and RSA-encryption methods inside the pad.
- Battery-free pen with changeable pen tip.
- Signature capturing with 500 Hz 4D samples and 1.024 pressure stages (x, y, z, t).
- Compatible with all currently available Windows- and Linux- systems.
- Compatible with Windows Remote Desktop and Citrix ICA environments.
- Secure Mode to display the signature on the screen in real-time.
- Delivery comes with completely assembled USB cable, pen and cord.
- Including free of charge software packages and SDK for several programming languages.



TECHNICAL DATA

General data

Dimensions	145 x 177 x 12 mm (H x W x T)
Casing colours	Upper shell: RAL 7021, black-grey Lower shell: RAL 9010, pure white
Cable port	USB
Cable length	Approx. 2,7 meters
Power consumption	Standby-status: 5 mA (HID/WinUSB) and 2 mA (FTDI) Consumption with LCD-Backlight: 75 mA Consumption without LCD-Backlight: 165 mA.
Power supply	USB
Status-LED	2 coloured and freely programmable LEDs
Stand	Mounting stand on the backside, compatible Multigrip™ plate available
Weight	Approx. 240 grams (incl. cable)
Warranty	2 years, optional extension up to 5 years.
Country of origin	Germany

Display

Type	Monochrome TFT
Size	4,5" (11,4 cm)
Colour space	Monochrome
Backlight	Optional, brightness: 150 cd/m ²
Configuration of backlight	The backlight can be configured with an API or configuration file.
Resolution	320 x 200 pixels \approx 84 x 84 ppi
Pixel size	0,285 mm
Visible area	97 x 61 mm
Line of sight	6 o'clock
Scroll-function	No

Sensor

Type	ERT (Electronic Resonance Technology)
Active signing area	96 x 60 mm
Resolution	9.598 x 5.998 pixels \approx 2.487 x 2.499 ppi
Linearity	\pm 0,4 mm
Method of input	Special sensor for pen input (no influence by hand touch).
Surface	Extremely durable, hardened special (anti-glare) glass.
Surface hardness	8H
Life expectancy	Approx. 30 million signatures
Pressure stages	1.024 pressure stages
Output rate of coordinates	500 Hz 4D-samples (consisting of x, y coordinates, time and pressure)
Internal sampling rate	6.000 samples per second
Pen	Active and battery-free pen with changeable pen tips.
Life expectancy of the pen	Approx. 1,2 million signatures at 250 grams pressure and 2,5 cm length.
Pen tilt angle	+/- 45°
Possible height of the pen	5 - 15 mm
Pen attachment	Highly flexible textile-cord and horizontal pen holder.

Connection types

USB	USB-HID and WinUSB
Serial	Optional with internal USB-Serial-Converter (VCOM-Port) using FTDI or chargeable VCOM-Port-Driver.
USB-Standby-Support	Yes, if the corresponding signal is given, the device switches off.
Ethernet	Yes, with an optionally available USB-to-Ethernet adapter.

Driver and software

Driver	No special driver is required for a USB connection.
Plug and Play	Yes, available for all connection types.
SDK (API)	SDK/API free of charge including updates and support.
Tools	Tools free of charge including updates and support.
Software	Further chargeable software available.

System environment

Operating System	Windows 7 and newer, Windows Server 2012 and newer, 32- and 64-Bit, Linux
Terminal Server and Citrix	Compatible with Windows Remote Desktop and Citrix ICA
Citrix Virtual Channel	Optionally available

Security mechanisms

Data transfer	AES-256 encrypted data transfer between host and pad via RSA key exchange.
Encryption	RSA-Encryption unit inside the pad.
Firmware	Flash memory is protected against data theft.
Secure Mode	Real-time display of the signature without usable biometrics.
Signature unit	RSA signature creation unit in the pad.
Key storage	Creation and storage of certificates in the pad.
Certificate Signing Request (CSR)	CSR can be generated in the pad and extracted.
Trusted certificates	The CSR can be signed by a root authority. Additional information: eIDAS Pad Signature Seal
Supported Hash-algorithms	SHA-1, SHA-256 and SHA-512
signotec „Content-Signing“	No
Protection against forceful break in	The casing can be glued optionally.

Miscellaneous

Transport protection	No
Individualization	Change of casing colour and logo print (on request).
Slideshow	The standby image is freely configurable.
Certifications and standards	CE, FCC, DIN EN 55032, DIN EN 55024, EN 62368-1)
RoHS	RoHS-compliant according to EU-regulations.
WEEE-Reg.-No. (German register for used devices)	DE 41995888
Packaging law Reg.-No.:	DE 3470684644700
Serial number	Unique and retrievable, internal serial number.
Device label	There is a label on the packaging and the device with information regarding the article number, hardware revision and serial number, including a barcode.

Operating and storage conditions

Operating temperature	-10°C to +60°C
Storage temperature	-25°C to +70°C
Air humidity for operation and storage	<= 90%, non-condensing
Air pressure for operation and storage	> 700 hPa
Degree of protection	IP 52

Reliability / Quality assurance

Quality test	Individual testing of devices with test log.
High temperature test of the components	240 hours at 80°C
Low temperature test of the components	240 hours at - 40°C
Humidity test of the components	240 hours at 60°C and 90% humidity
Thermal shock test of the components	30 minutes at - 40°C and directly 30 minutes at + 80°C (10x in succession)

Article numbers

Without LCD-Backlight

ST-ZMERT-3-U100	signotec Zeta with USB and approx. 2,7 m USB-cable
ST-ZMERT-3-FT100	signotec Zeta with virtual COM-Port via USB and approx. 2,7 m USB-cable (USB 2serial)

With LCD-Backlight

ST-ZBERT-3-FT100	signotec Zeta Backlight with USB and approx. 2,7 m USB-cable
ST-ZBERT-3-FT100	signotec Zeta Backlight with virtual COM-Port via USB and approx. 2,7 m USB-cable (USB 2serial)

Copyright

Copyright © 2000 - 2020 signotec GmbH

All rights reserved. This documentation and the components described therein are copyrighted products of signotec GmbH Ratingen in Germany. Partial or full reproduction is only permitted with the written consent of signotec GmbH. All hardware and software names used are trade names and / or trademarks of the respective manufacturers / owners. Subject to changes at any time. We accept no liability for errors in the documentation.