



DSP-V9

DSP-V9 Series

90mm Character High

VFD Customer Display

A Smart and Powerful Customer Display that Not only Looks Good



Restaurant
Auto System



Easypos
System



Mobile
Pos System

1. 90mm character high and Japan-made VFD tube

In an increasingly competitive market, Birch releases the DSP-V9 customer display with Japan-made VFD tube supports 90mm character high, and with performance features to support your business

2. A fresh sense of glamour

DSP-V9 customer display features a fresh glamour and modernity in its design. The true-flat design display screen and excellent base design bring you a sense of contemporary feeling

3. Blessed with powerful capabilities

DSP-V9 customer display supports big characters(5 x 7 dot matrix character font, 9.03(H) x 5.25(W)mm high, 0.85 x 1.05mm dot size) and powerful functions as below:

- Support 11 command modes which includes Epson.
- Support 5V power (optional for 12V or 24V)
- Support OPOS/JavaPOS drivers as standard.

4. Durability and Unrivalled Convenience

- The display of DSP-V9 is viewing angle changeable (up, down and rotation) with Metal hinge device to assure of the viewing angle durability.
- DSP-V9 support multiple languages.
- Built-in Japan-made VFD module with MTBF hours: 30,000 hrs.

Ordering Information:

- DSP-V9FBU: 20x 2 line VFD customer display, USB(VirtualCOM)
- DSP-V9FBR: 20 x 2 line VFD customer display, RS232



Technical Specifications

●General:

Display method:

Vacuum fluorescent display (VFD)

Display color: Blue Green

Number of characters:

40 characters; 20 columns x 2 lines

Brightness: 500~1000 cd /m²

Character font: 5 x 7 Dot matrix

Character size: 9.0mm x 5.25mm

Character type:

I. 95 alphanumeric;

II. 32 sets of international characters:

FRANCE、GERMANY、U.K、
DENMARKI、SWEDEN、ITALY、
SPAIN、JAPAN、NORWAY、
DENMARKII、SLAVONIC、
RUSSIA、Portuguese、Canadian
French、Nordic、Turkish、Greek、
West European Latin、CP858、
CP860、WPC1252、
CP857(TURKISH)、polish、
wpc1250、wpc1253 (GREEK)、
wpc1255 (Hebrew)、wpc1251、
CP866、CP852、CP737
(DOSgreek)、CP858、CP864
(Arabic)、Farsi (Iran)

●Interface

USB

RS232 (Serial)

●Reliability:

MTBF: 30,000 hours

●Power:

Power supply: DC 5V~24V DC

Power consumption: 3W Average
Maximum 15W

●Dimension:

Head (W x D x H): 200 x 77.5 x 31 mm

Pole Dimension: Per support length:
140(L) x 34.5(Dia)mm

Base (W x D x H): 169.5 x 98.5 x 39mm

Weight: N.W. 0.98kg

Viewing Angle : Max. 90°

Horizontal Rotation : Max. 355°

●Command Mode:

LD220, EPSON POS D101, AEDEX, UTC/S,
UTC/P, ADM788, DSP800, CD5220, EMAX,
LOGIC CONTROL

●Environment

EMC & Safety : CE/FCC Class B/RoHS

Operation Temperature : 10~40°C

Storage Temperature : -10~50°C

Operation Humidity : 0%~90% RH

Storage Humidity : 0%~90% RH

●Mechanical

Housing Color : Black



Birch is a trademark of Birch Technology U.S.A. Inc
All other products, brands or companies are trademarks or registered
trademarks of their respective companies.

Specifications are subject to change without prior notice

Contact us for details